



For the Account of: Pierre Frey Inc.  
1704 Chantilly Dr. NE  
Suite 200  
Atlanta, GA 30324

Client's Identification: F4063 FERSEN

## CERTIFICATE OF TESTING

**TEST PERFORMED:** NFPA 260 Standard Methods of Tests and Classification System for Cigarette Ignition Resistance of Components of Upholstered Furniture – 2024; Fabric Cover Test

### TEST RESULTS

| Specimen | Char Length (in) | Extinguished in 45 Minutes |
|----------|------------------|----------------------------|
| 1        | 0.5              | Yes                        |
| 2        | 0.6              | Yes                        |
| 3        | 0.5              | Yes                        |

### NOTES

**Test Conditions:** 70 ±4°F, 65 ±5% Relative Humidity  
**Test Environment:** 70 ±4°F, 50 ±5% Relative Humidity  
**Sampling:** As Received  
**Ignition Source:** SRM 1196a  
**Abbreviations:** SE = Self-extinguished      OBV = Obvious ignition of substrate

### ACCEPTANCE CRITERIA

1. If the test specimen has no ignition, or if no individual specimen yields a vertical char of 45 mm (1.75 inches) or greater, the fabric is classified a Class I cover fabric.
2. If the vertical char of any test specimen is greater than 45 mm (1.75 inches), the fabric is classified a Class II cover fabric.
3. If the smoldering extends beyond 45 minutes after placement of the cigarette, the fabric is classified as a Class II cover fabric.
4. If an obvious ignition of the polyurethane substrate occurs on the test assembly, the fabric is classified a Class II cover fabric.

**CONCLUSION** Based on the above Results and Acceptance Criteria, the item tested is:

- Class I  
 Class II

**CERTIFICATION** I certify that the above results were obtained after testing specimen in accordance with the procedures and equipment specified by the standard stated above.

Authorized Signature

Date Order Completed: 04/16/2025